

---

---

# 10.3. LAB Meeting

— R04922001 李朋軒 —

R04922023 屠政皓

---



---

# Motivation

- Ambient sensor is good at localization and capture global condition, earable sensor is good at recognize human body trace
- Daily lives data is not segmented, but grammar based model can find pattern in infinite stream conveniently
- Sensor with good segmentation,


# Related work

<i>Activity level classes</i>	<i>Activities</i>
<b>1- Very Low Level Activities</b>	Sleeping, sitting still and lying down
<b>2- Low Level Activities</b>	Reading, sitting, eating, measuring weight or blood pressure, drinking, watching television and talking
<b>3- Medium Level Activities</b>	Preparing food, walking, sitting down and getting up, wearing clothes, washing up, ironing, non-intense house-work, opening doors, lying down and getting up
<b>4- High Level Activities</b>	Running, sports and intense house-work



Atallah, Louis, et al. "Real-time activity classification using ambient and wearable sensors." *Information Technology in Biomedicine, IEEE Transactions on* 13.6 (2009): 1031-1039.

# Method



- Using model with low false negative rate to segment some possible time interval
- Using another model to do more accurate recognition on wearable sensor

# Plan

- Use R324 PIR, Light, Magnetic sensors
- A person with 6-axis accelerometers on his/her hands and legs
- Recognize the following activities:
  - wandering, eating lunch, using computer, sleeping, sweeping, using cell phone, leaving, entering
- Label training data with cell phone


# Feature-Based SCFG

SCFG, Merge, Chunk, GMM

# Context-Free Grammar

- Nonterminal
  - S, NP, VP, ...
- Terminal
  - The, boy, see...
- Rule
  - (VP, VP, PP)
  - (VP, V, NP)
  - ...
- Start Symbol
  - S


A parse (tree) of some CFG



# Stochastic CFG

- CFG rules of VP = {(VP, VP, PP), (VP, VP, NP)}
- SCFG rules of VP = {(VP, VP, PP): 0.7, (VP, VP, NP): 0.3}

The probability of the parse:  
 $0.5 * 0.9 * 0.7 * \dots$



# Learning A Grammar Structure


- Corpus
  - I ate a cat
  - Bob drank blood
  - ...
- Naïve rules
  - Add (S, I, ate, a, cat), (S, Bob, drank, blood), ...
  - 我的grammar都沒有片語，改成記錄所有看到的句子，用起來跟KNN有90%像
- Merge and chunk
  - Add (VP, ate), (VP, drank)
  - Add (NP, a, cat), (NP, blood)
  - Add (NEW, VP, NP)

# Uncertainties in Input Symbols

	Capital	Letters	Height
The	1	3	2
Boy	0	3	3
	0.7	3	3


- Feature vectors as symbols
  - The = [1,3,2]
  - boy = [0,3,3]
  - Input = [0.7,3,3]
- Scan probability
  - Cosine similarity
  - Gaussian distribution

The or boy? ←





# Gaussian Mixture Model

- The =  $\{[1,3,2]:0.86, [0.7,3,2.5]:0.11, [1,2,2]:0.03\}$
- $X\_POS = \{ \circ : 0.xx \mid \circ \in Dotted\_image \}$





# Probability Contour of X\_POS



# Time Series Data

- Recognize legitimate sentences in indefinitely long data stream



Guts kneed I ate glasses a cat high **Bob** a **drank blood** saw YOLO...

FSCFG:

terminal list:

```
[t34] weight=-0.915332
      -0.01 -1.33 -2.23 [2]
      -0.01  1.40 -1.75 [8]
[t16] weight=-0.683536
      -1.40  0.00 -0.74 [25]
      -1.33  0.00  1.66 [11]
      -1.36  0.00  0.36 [25]
      -1.51  0.00  0.90 [16]
      -1.44  0.00 -1.74 [7]
      -1.38  0.00 -0.22 [22]
[t6] weight=-0.722681
      -0.01 -1.45  1.11 [17]
      -0.01 -1.43  0.37 [15]
      -0.01 -1.34 -0.72 [16]
      -0.01 -1.39  1.64 [11]
      -0.01 -1.42 -0.20 [28]
      -0.01 -1.33 -2.23 [2]
      -0.01 -1.42 -1.41 [15]
[t0] weight=-0.63464
      -0.01  1.44  0.20 [23]
      -0.01  1.43 -1.00 [17]
      -0.01  1.37  1.57 [14]
      -0.01  1.36 -0.47 [25]
      -0.01  1.40  0.74 [19]
[t12] weight=-0.804574
      1.32  0.00 -0.96 [19]
      1.35  0.00  2.30 [8]
      1.47  0.00  1.24 [13]
      1.54  0.00 -1.95 [10]
      1.41  0.00  0.26 [22]
      1.43  0.00  0.78 [14]
      1.40  0.00 -0.30 [20]
```

nonterminal list:

```
[N085] cnt=98
[N080] cnt=104
[N087] cnt=106
[N083] cnt=106
[N067] cnt=10
[N000] cnt=106
start symbol:
[N000] cnt=106
rule:
[ 98  0.00 ] N085 -> t0
[ 104  0.00 ] N080 -> t6
[ 106  0.00 ] N087 -> t16
[ 106  0.00 ] N083 -> t12
[ 10  0.00 ] N067 -> t34
[ 16 -1.89 ] N000 -> N083 N080 N087 N085
[ 1 -4.66 ] N000 -> N083 N067 N087 N085
[ 1 -4.66 ] N000 -> N080 N087 N067 N083
[ 2 -3.97 ] N000 -> N087 N067 N083 N080
[ 1 -4.66 ] N000 -> N083 N067 N087 N067
[ 2 -3.97 ] N000 -> N067 N083 N080 N087
[ 27 -1.37 ] N000 -> N087 N085 N083 N080
[ 27 -1.37 ] N000 -> N085 N083 N080 N087
[ 2 -3.97 ] N000 -> N083 N080 N087 N067
[ 27 -1.37 ] N000 -> N080 N087 N085 N083
```

119882328 function calls (113851494 primitive calls) in 71.683 seconds

# References

- Stolcke, A. (1995). An efficient probabilistic context-free parsing algorithm that computes prefix probabilities. *Computational linguistics*, 21(2), 165-201.
- Stolcke, A. (1994). *Bayesian learning of probabilistic language models*(Doctoral dissertation, University of California, Berkeley).
- Ivanov, Y., & Bobick, A. F. (2000). Recognition of visual activities and interactions by stochastic parsing. *Pattern Analysis and Machine Intelligence, IEEE Transactions on*, 22(8), 852-872.
- Sadeghipour, A., & Kopp, S. (2014, June). A Hybrid Grammar-Based Approach for Learning and Recognizing Natural Hand Gestures. In *Proceedings of the 28th AAAI conference on artificial intelligence*.